

## CLAIMS

1 1. (Currently Amended) A rebar spacer comprising,  
2 a one clip having a bottom portion with a semicircular rebar cradling portion,  
3 a pair of columns one on either side of the semicircular rebar cradling portion and  
4 extending upward therefrom,  
5 a cross portion on each column extending toward the opposing column,  
6 a straight arm extending angularly downward from each cross portion toward the  
7 axis of the radius of the semicircular rebar cradling portion and having an end proximate  
8 a rebar placed in the cradling portion,  
9 a shoulder portion on each side of the semicircular rebar cradling portion,  
10 between the semicircular rebar cradling portion and the columns, each shoulder portion  
11 having a width at least the width of the arm, to allow the arm to be recessed over the  
12 shoulder,  
13 a base portion attached to the base of the clip for supporting the clip at a desired  
14 height, the clip being centered over the middle of the length and width of the base  
15 portion.

1 2. (Original) A rebar spacer as in claim 1 wherein,  
2 the base portion has a flat base,  
3 a left wall extending from the flat base to the bottom of the clip and center wall  
4 extending from the base to the bottom of the clip and a right wall extending from the flat  
5 base to the bottom of the clip.

1 3. (Original) A rebar spacer as in claim 2 wherein,  
2 The left and right walls are slanted inward from the edge of the flat base to the  
3 sides of the clip, and the center wall is perpendicular to the flat base and the base of the  
4 clip.

1 4. (Withdrawn) A rebar spacer as in claim 2 wherein,  
2 a cross wall extends between the flat base and the bottom of the clip, between the  
3 right wall and the center wall and between the left wall and the center wall.

1 5. (Withdrawn) A rebar spacer as in claim 1 wherein,  
2 a left leg extending from the bottom of the clip, center wall extending from the  
3 bottom of the clip and a right leg extending from the bottom of the clip,  
4 a cross brace from the center wall to the left leg and a cross brace from the center  
5 wall to the right leg.

1 6. (Withdrawn) A rebar spacer as in claim 5 wherein,  
2 The center wall has feet extending below the wall.

1 7. (Withdrawn) A rebar spacer as in claim 2 wherein,  
2 the flat base has feet thereunder.

1 8. (Withdrawn) A rebar spacer as in claim 1 wherein,  
2 the base portion has a flat base thereunder, the flat base has a left wall, a right  
3 wall and a cross wall extending between the left and right walls with the clip integral with  
4 the cross wall such that the “U” shaped rebar receiving portion receives the rebar between  
5 the left and right walls.

1 9. (Withdrawn) A rebar spacer as in claim 8 wherein,  
2 the base has feet thereunder.

1 10. (Withdrawn) A rebar spacer as in claim 8 wherein,  
2 the flat base has a portion of the base between the left and right walls removed.

1 11. (Withdrawn) A rebar spacer as in claim 10 wherein,  
2 the base has feet thereunder.